

## MATERIAL SAFETY DATA SHEET



EXQ Company

471-23, Songjeong-Ri, Mado-Myun, Hwasung-Si, Gyeonggi-Do, Korea Rep.

Tel) 82-505-878-8080

Fax) 82-505-899-8080

Copyright, 2008, EXQ Co. All right reserved. Copying and/or downloading of this information for the purpose of properly utilizing EXQ products is allowed provided that ;

1) the information is copied in full with no changes unless prior agreement is obtained from EXQ and

2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### 1. PRODUCT AND COMPANY IDENTIFICATION

DIVISION : AUTOMOTIVE MARKET

TRADE NAME : SN1071 #7000 Dark Compound

ISSUED : September 1, 2009

COMPANY : EXQ Company

471-23, Songjeong-Ri, Mado-Myun, Hwasung-Si, Gyeonggi-Do, Korea Rep.

Tel) 82-505-878-8080

Fax) 82-505-899-8080

#### PRODUCT USE:

Intended Use : To remove haze generated by compound material in removing defects of painted auto parts.

Specific Use : Glaze

### 2. INGREDIENT

Ingredient

CAS No.

% by wt.

Aluminum oxide	1344-28-1	1% - 9%
Silica	7631-86-9	3% - 12%
D.I. Water	7732-18-5	35% - 60%
White mineral spirit	64741-89-5	0% - 6%
Hydrotreated heavy naphtha (Petroleum)	64742-48-9	23% - 37%
Acrylic polymer	70425-89-7	1% - 6%
Surfactant	trade secret	0% - 4%
Carbon black	1333-86-4	q'ty required

### 3. HAZARDS IDENTIFICATION

#### EYE CONTACT:

Liquid may be irritating to the eyes upon direct contact. Symptoms overexposure can include one or more of the following: redness, tearing, irritation, burning sensation.

#### SKIN CONTACT:

Prolonged skin contact may defat skin leading to irritation or dermatitis.

#### INHALATION:

Vapors may be irritating to the respiratory system. Prolonged overexposure to vapors may cause kidney effects and may cause central nervous system effects.

#### INGESTION:

May cause digestive system irritation. Aspiration into lungs may cause lung damage.

### 4. FIRST AID MEASURES

#### EYE CONTACT:

Flush eyes with plenty of water. If signs/symptoms persist, get medical attention.

#### SKIN CONTACT:

Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

#### INHALATION:

Remove person to fresh air. If signs/symptoms develop, get medical attention.

#### IF SWALLOWED:

Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

#### OTHER FIRST AID:

None

### 5. FIRE FIGHTING MEASURES

FLASH POINT: No data available

FLAMMABLE LIMIT - LEL: No data available

FLAMMABLE LIMIT - UEL: No data available

AUTOIGNITION TEMPERATURE: No data available

#### EXTINGUISHING MEDIA:

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

#### SPECIAL FIRE FIGHTING PROCEDURES:

Treat as oil fire. Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protection equipment(Bunker Gear) and a self-contained breathing apparatus(SCBA).

#### UNUSUAL FIRE AND EXPLOSION HAZARDS:

Not applicable. Closed containers exposed to heat from fire may build pressure and explode. Vapor may travel long distances along the ground or floor to an ignition source and flash back.

### 6. ACCIDENTAL RELEASE MEASURES

Observe precautions from other sections. Extinguish all ignition sources and ventilate area. Cover with absorbent material. Place in an approved metal container and seal.

### 7. HANDLING AND STORAGE

HANDLING : Keep out of the reach of children. Avoid eye contact. Avoid breathing of

vapors or mists. Do not eat, drink or smoke when using this material. Wash exposed area with soap and water. Keep container closed when not in use. Keep away from heat, sparks, open flame and other sources of ignition. Contents may be under pressure, open carefully.

STORAGE : Keep container tightly closed. Store away from heat. Keep container in well-ventilated area. Do not allow to freeze.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Use with appropriate local exhaust ventilation.

### EYE/FACE PROTECTION

Avoid eye contact.

The following eye protection is recommended : Safety Glasses with side shields.

### SKIN PROTECTION

Avoid prolonged or repeated skin contact.

Select and use gloves and/or protective clothing to prevent skin contact.

### RESPIRATORY PROTECTION

Avoid breathing of vapors or mists.

### PREVENTION OF SWALLOWING

Do not eat, drink or smoke when using this product. Wash exposed areas with soap and water.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC PHYSICAL FORM	Emulsion
ODOR, COLOR	Little odor, Charcoal creamy liquid,
GENERAL PHYSICAL FORM	Liquid
BOILING POINT:	212 F
VAPOR PRESSURE:	N/D
VAPOR DENSITY:	N/D
EVAPORATION RATE:	N/D

SOLUBILITY IN WATER:	dilutable
SPECIFIC GRAVITY:	0.95 - 1.10 Water=1
PERCENT VOLATILE:	75.0 - 85.0%
pH:	7.2 – 9.2
VISCOSITY:	2000 - 9000 CPS

## 10. STABILITY AND REACTIVITY

STABILITY: Stable

INCOMPATIBILITY - MATERIALS TO AVOID: Strong oxidizing agents.

HAZARDOUS POLYMERIZATION: will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, Carbon dioxide, Smoke particles.

## 11. TOXICOLOGICAL INFORMATION

No data available.

## 12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION : No data available.

CHEMICAL FATE INFORMATION : No data available.

## 13. DISPOSAL CONSIDERATIONS

Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

#### 14. TRANSPORT INFORMATION

Protect from the shock.

DOT, IATA, IMDG

This product does not meet the definition of any hazard class and therefore is not subject to DOT, IATA, and IMDG Regulations.

#### 15. REGULATORY INFORMATION

INDUSTRIAL SAFETY & HEALTH ACT : No data available.

INTERNATIONAL REGULATIONS : No data available.

#### 16. OTHER INFORMATION

This MSDS has been prepared to meet the Industrial Safety & Health Act, Korea Occupational Safety and Health Agency(KOSHA)

The information in this Material Safety Data Sheet(MSDS) represents our current data and best opinion as to the proper use in handling of this material under normal conditions. Any use of the material in combination with any other material or any other process is the responsibility of the user.